

818v3

REFERENCE AUDIO CORE



OVERVIEW

The 818v3 is the highest performance two-channel preamplifier manufactured by Meridian – the ultimate home audio system hub. Connecting at the heart of an incredible Meridian music system, it offers simple networked integration with an array of audio sources, including MQA-encoded files and streams.

Since its introduction in 1998, Meridian's 800 Reference Series has showcased the very best in surround sound, DVD, CD, and network music playback, becoming the benchmark against which performance standards have been set throughout the audio industry.

PRODUCT HIGHLIGHTS

Reference preamplifier featuring Meridian enhancement technologies such as FIFO buffering, DSP upsampling and apodising filters to deliver the very best performance from any digital source.

- Works within a Roon system to provide an audio end-point of the highest quality.
- Full range of analogue and digital inputs allowing the 818v3 to handle all your sources, with Meridian enhancements on the digital inputs. Standby mode maintains voltage rails for instant warm-up.
- Magnetically isolated design maximises audio quality.
- Meridian SpeakerLink connection for ultimate quality and convenience of installation when driving Meridian DSP Loudspeakers.

CONSTRUCTION

Finished in high grade materials, the 818v3 features sculptured end panels which mirror the soft lines of Meridian's DPS Loudspeakers.

The 818v3 is available in black and the full range of Meridian Select colour options.

- The 818v3 Reference Audio Core features an advanced linear power supply design for minimum noise and maximum signal integrity.
- SpeakerLink helps make a Meridian system easier to install and far less intrusive than other high-end audio systems.
- An enhanced analogue output card features advanced filtering for broader bandwidth, maximising the potential of high-resolution music.

SPECIFICATION

OUTPUTS - Analogue	<ul style="list-style-type: none"> • 1x unbalanced on phono, 1x balanced on XLR-3M, rendering of decoded MQA streams
OUTPUTS - Digital	<ul style="list-style-type: none"> • Coaxial S/PDIF $\leq 96\text{kHz}/24\text{-bit}$ • Twin SpeakerLink, RJ45 balanced (AES/EBU) digital interface for single-cable connection to other Meridian equipment, $\leq 96\text{kHz}/24\text{-bit}$ with MHR, and MQA signals for rendering by Meridian DSP loudspeakers
INPUTS - Analogue	<ul style="list-style-type: none"> • 6x unbalanced on phono
INPUTS - Digital	<ul style="list-style-type: none"> • 2x Coaxial S/PDIF $\leq 192\text{kHz}/24\text{-bit}$, DoP, 2x Toslink optical $\leq 96\text{kHz}/24\text{-bit}$, 1x SpeakerLink $\leq 192\text{kHz}/24\text{-bit}$, 1x Asynchronous USB $\leq 192\text{kHz}/24\text{-bit}$, DoP, MQA source decoding, DSD (DoP) native decode
SOURCES	<ul style="list-style-type: none"> • Meridian Sooloos System: RJ45 Ethernet connection
COMMS	<ul style="list-style-type: none"> • Meridian Comms: 2x 240 degree 5-pin DIN, 1x SpeakerLink input with Comms, 2x SpeakerLink outputs with Comms • RS232: 9-pin D-sub, remote control & configuration • Triggers: 3x 12V (barrel connectors)
CONTROLS	<ul style="list-style-type: none"> • Front panel: Source, Play/Pause, Previous, Next, Mute, Volume+, Volume-, Off • Behind long door: Menu, Up, Down, Left, Right, F-Fwd, F-Rwd, Setup, Source, Display, Mute, Volume+, Volume- • Remote Control: Via MSR+ (supplied) and RS232
DISPLAY	<ul style="list-style-type: none"> • 20-character LCD: With adjustable brightness and contrast
DIMENSIONS/WEIGHT	<ul style="list-style-type: none"> • HEIGHT: 175mm [6.9in] • WIDTH: 480mm [18.9in] • DEPTH: 411mm [16.2in] • WEIGHT: 16.0kg [35.2lbs]
POWER	<ul style="list-style-type: none"> • Advanced linear power supply: 110 - 120 Volt 50/60Hz, 220 - 240 Volt 50/60Hz • Max Power Consumption: 40 Watts